



VITRIPIAZZA®

Vitrified Porcelain Paving

Declaration of Performance

Vitripiazza Sofia

No. Sofia2021V1

1. Unique identification code of the product type:

Dry-pressed porcelain tiles, with water absorption Eb ≤ 0,5%

2. Intended use:

For internal and external floorings and walls

3. Name or registered trade mark, and contact address of the manufacturer:

Ceramica de/ Conca S.p.a. - Via Croce, 8 – 47832 San Clemente (RN) - ITALY

4. System of assessment and verification of constancy of performance (AVCP):

System 4

5. Name and identification number of notified laboratory, if relevant:

Not Relevant

6. Declared performances:

| Essential characteristics | Performance | Harmonized technical specification |
|---------------------------------------|----------------------|------------------------------------|
| Reaction to fire: | A1 _{FL} /A1 | EN 14411:2012 |
| Release of dangerous substances. for: | | |
| Cadmium: | NPD | |
| Lead: | NPD | |
| Breaking strength: | > 1300N | |
| Slipperiness: | See table below | |
| Tactility | NPD | |
| Bond/Strength adhesion, for: | | |
| Cementitious adhesive, type C2: | 1 N/mm ² | |
| Thermal shock resistance: | Pass | |
| Durability for: | | |
| Internal use: | Pass | |
| External use (freeze/thaw resistance) | Pass | |

| RANGE | DIN51130 | DIN51097 | UNE-ENV 12633:2006 | BCRA | BS 7976:2002 | |
|-------|----------|----------|--------------------|-----------|--------------|-----|
| | | | | Dry >0,40 | N/A | N/A |
| Sofia | R11 | C | N/A | Wet >0,40 | | |

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer declared in point 3.

Signed for and on behalf of the manufacturer by: Luca Costi - CEO

Place and date of issue: San Clemente

Signature:

21/10/19