



VITRIPIAZZA®

Vitrified Porcelain Paving

# Declaration of Performance

## Vitripiazza Bellstone

No. Bellstone2021V3

**1. Unique identification code of the product type:**

Dry-pressed Ceramic tiles, with water absorption Eb ≤ 0,5%

**2. Intended use:**

For internal and external floorings and walls

**3. Name or registered trade mark, and contact address of the manufacturer:**

Talasey Ltd, St Vincent House, Normanby Road, Scunthorpe, DN15 8QT

**4. System of assessment and verification of constancy of performance (AVCP):**

System 4

**5. Name and identification number of notified laboratory, if relevant:**

Not Relevant

**6. In case of the declaration of performance concerning a construction product covered by a designated standard**

BS EN 14411:2012

**7. Declared performances:**

Essential characteristics	Performance	Standard for Test Method
Reaction to fire:	A1FL/A1	EN ISO 10545
Release of dangerous substances. for:		
Cadmium:	>0.07 mg/dm <sup>2</sup>	
Lead:	>0.08 mg/dm <sup>2</sup>	
Breaking strength:	> 1300N	
Slipperiness:	See table below	
Tactility	NPD	
Bond/Strength adhesion, for:		
Cementitious adhesive, type C2:	NPD	
Thermal shock resistance:	Pass	
Durability for:		
Internal use:	Pass	
External use (freeze/thaw resistance)	Pass	

RANGE	DIN51130	DIN51097	UNE-ENV 12633:2006	BCRA	BS 7976:2002	
					Dry	Wet
Bellstone	R11	A+B+C	N/A	N/A	PTV > 36	PTV > 36

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer declared in point 3.

Signed for and on behalf of the manufacturer by: Lavinia Dowson Technical and Training Manager

Place and date of issue: Scunthorpe, UK

Signature:

April 2018